



EXPLOSION PROOF AIR CONDITIONERS

Schedule "A"

SafetyCool Window or Thru-Wall Air Conditioners 50 Hertz

COOLING ONLY, 50 Hz,^(1,4) NEC Class I, Groups B⁽⁸⁾, C and D, Division 2

MODEL	COOL ⁽³⁾	VAC	FUSE	HEIGHT ⁽⁵⁾	WIDTH ⁽⁵⁾	DEPTH ⁽⁵⁾	WEIGHT ⁽⁶⁾
	BTUH		AMPS	INCHES	INCHES	INCHES	NETLBS
WACX-50-1234	12,000	220/240	15	15-0/0	23-5/8	22-1/16	125
WACX-50-1804	18,000	220/240	15	16-15/16	26-0/0	30-3/8	150
WACX-50-2404	24,000	220/240	20	16-15/16	26-0/0	30-3/8	160

COOLING AND ELECTRIC HEAT,^(1,2,) 50⁽⁴⁾ Hz, NEC Class I, Group B⁽⁸⁾ and D, Division 2

MODEL	COOL ⁽³⁾⁽⁷⁾	HEAT ⁽³⁾	VAC	FUSE	HEIGHT ⁽⁵⁾	WIDTH ⁽⁵⁾	DEPTH ⁽⁵⁾	WEIGHT
	BTUH	BTUH		AMPS	INCHES	INCHES	INCHES	NETLBS
WACX-50-1234-EH-0968	12,000	9,596	220/240	20	15-0/0	23-5/8	42-3/4	285
WACX-50-1234-EH-1398	12,000	13,435	220/240	25	15-0/0	23-5/8	42-3/4	285
WACX-50-1804-EH-1291	18,000	11,516	220/240	20	16-15/16	26-0/0	42-3/4	305
WACX-50-1804-EH-1936	18,000	19,193	220/240	30	16-15/16	26-0/0	42-3/4	305
WACX-50-2404-EH-1828	24,000	17,273	220/240	30	16-15/16	26-0/0	42-3/4	320
WACX-50-2404-EH-2366	24,000	23,031	220/240	35	16-15/16	26-0/0	42-3/4	320

- (1) Manufacturer certified, not CSA listed. Heaters rated for NEC Identification Code T2A. Suitable for use in hazardous locations containing compounds with ignition temperatures of 536°F (280°C) or higher.
- (2) Free-standing, UL or CSA listed Electric Heaters are also available. These are rated for Class I, Groups C or D and Class II, Groups E, F, and G with NEC Identification Numbers T2A, T2B or T3B. (Bulletin EXHE1PSS).
- (3) 220/240 models are rated at 240 Volts. Deduct 16% for heater rating at 208 Volts.
- (4) For 60 Hz models request Price List SAEX6PRL.
- (5) **Request certified drawings before making cutouts!** Dimensions subject to change.
- (6) Add 35 lbs. for cardboard domestic, 55 to 70 lbs. for air crate, or 110 to 170 lbs. for sea crate.
- (7) Rated at 95°F (35°C) dry bulb temperature. SafetyCool models are designed to also operate effectively at higher ambients. At 120°F (49°C) outside dry bulb temperature the cooling capacity is reduced approximately 22 percent.
- (8) For Group B add "/RC/IB2" to model number and add US\$ 1,322. to price for models up through 12,000 BTUH and add US\$ 1,939. for models rated higher than 12,000 BTUH. Control box is external.



**SCIENTIFIC
SYSTEMS
LLC**

SEE CONTINUED FOR OPTIONS AND ACCESSORIES



(Continued from other Side)

OPTIONS AND ACCESSORIES

- LAC Low Ambient Controls for operating air conditioner at outdoor ambient temperatures below 55°F (13°C) .
- BG **BLYGOLD Polual** spray applied coating on condenser and evaporator coils, additional
- ECB **BLYGOLD Polual** spray applied coil coating, other metal epoxy primed and coated, additional
- SH Cover Housing, Corrosion Resistant Type 316 stainless steel
- MBS Mounting Bracket Set, stainless steel, for extra strong support of **SafetyCool** cabinets
- EXP Export Crate, for rough handling, choice of sea or air crate, specify⁽²⁾
- RC Remote Controls, thermostat and selector switch
- SPS Spare Parts Kit⁽¹⁾ (thermostat, selector switch, run capacitor)
- CC **SaveCoil 101** Dip applied and baked coating on condenser and evaporator coils, additional
- EC **SaveCoil 101** Dip applied and baked coil coating, other metal epoxy primed and coated, additional
- CuCu Condenser and Evaporator Coil Copper Tubes with Coper Fins for 8,400 btu thru 24,000 btu, additional .
- CuCu Condenser and Evaporator Coil Copper Tubes with Coper Fins for 28,000 btu and 35,000 btu, additional

- (1) Kit available for shipment **with** air conditioner only. Use numbers from Parts List for replacement parts ordered later.
- (2) Add 35 lbs. for cardboard, 55 to 70 lbs. for air crate, or 110 to 170 lbs. for sea crate.
- (3) For Group B add "/RC/IB2" to model number and add US\$ 1,322. to price for models up through 12,000 BTUH and add US\$ 1,939. for models rated higher than 12,000 BTUH. Control box is external.

We reserve the right to modify and improve our products. Prices and specifications are subject to change!

3-YEAR LIMITED WARRANTY

SafetyCool air conditioners are warranted to be free of defects in materials and workmanship for a period of three (3) years. During the first twelve months following date of shipment Scientific Systems will repair or replace any defective component at no charge. For the next two years Scientific Systems will repair or replace any non-functional item or items for a total cost not to exceed (50) percent of the list price of an equivalent model air conditioner. Items returned for repair or replacement must be shipped to factory with freight prepaid and will be returned freight collect. This warranty applies to the original, registered customer only. Items damaged during shipment or as a result of improper handling or use are specifically excluded under this warranty.

