



## How to Order

Model <sup>(1)</sup>	Cool	Heat <sup>(2)</sup>	Air Flow	Power	Fuse	Weight	Price
	BTUH	BTUH @ 47°F	CFM (E.S.P.)	Volts / Phase	Max. Amp	Ship Lbs.	US \$
VACX - 018 - B - ID2	18,300		650 (0.4)	208/230/1	20	350	8,270.
VACX - 024 - B - ID2	24,000		800 (0.2)	208/230/1	20	350	8,290.
VACX - 024 - C - ID2	24,000		800 (0.2)	208/230/3	15	350	8,365.
VACX - 036 - B - ID2	36,000		1100 (0.3)	208/230/1	35	400	8,675.
VACX - 036 - C - ID2	36,000		1100 (0.3)	208/230/3	25	400	8,775.
VACX - 036 - D - ID2	36,000		1100 (0.3)	460/3	15	400	9,120.
VACX - 048 - C - ID2	47,500		1550 (0.2)	208/230/3	35	550	9,775.
VACX - 048 - D - ID2	47,500		1550 (0.2)	460/3	15	550	9,895.
VACX - 060 - C - ID2	57,500		1700 (0.3)	208/230/3	45	550	10,170.
VACX - 060 - D - ID2	57,500		1700 (0.3)	460/3	20	550	10,295.
VACX - 018 - HP - 018 - B - ID2	19,000	18,800	650 (0.4)	208/230/1	20	350	9,510.
VACX - 024 - HP - 024 - B - ID2	23,600	23,200	800 (0.2)	208/230/1	20	350	9,555.
VACX - 024 - HP - 024 - C - ID2	23,600	23,200	800 (0.2)	208/230/3	15	350	9,640.
VACX - 036 - HP - 036 - B - ID2	35,600	34,400	1100 (0.3)	208/230/1	35	400	9,910.
VACX - 036 - HP - 036 - C - ID2	35,400	34,200	1100 (0.3)	208/230/3	25	400	10,050.
VACX - 036 - HP - 036 - D - ID2	35,400	34,200	1100 (0.3)	460/3	15	400	10,170.
VACX - 048 - HP - 048 - C - ID2	47,000	46,000	1550 (0.2)	208/230/3	35	550	10,950.
VACX - 048 - HP - 048 - D - ID2	47,000	46,000	1550 (0.2)	460/3	15	550	11,070.
VACX - 060 - HP - 060 - C - ID2	56,500	58,000	1700 (0.3)	208/230/3	45	550	11,435.
VACX - 060 - HP - 060 - D - ID2	56,500	58,000	1700 (0.3)	460/3	20	550	11,555.

(1) = Explosion Proof NEC Class I, Group D, Division 2. If specified otherwise, change "ID2" to new specification, e.g., "IC2".

(2) = Explosion proof heat pumps do not have supplemental electric heat. They are not recommended for use below 45 °F.

## Dimensions

VACX	Width	Depth	Height	Supply Air Opening	Return Air Opening
	inches	inches	inches	inches	inches
-018, -024	30	18-1/4	66-1/2	8 H x 20 W	12 H x 20 W
-036,	38	18-1/4	66	8 H x 28 W	14 H x 28 W
-048, 060	43	22	81-5/8	10 H x 30 W	16 H x 30 W

## Accessories and Options

TCXP-C-1101	Thermostat, "Cool" or "Fan Only", Class I and II, Groups B, C and D. ....	1085.
TCXP-HC-1101	Thermostat, "Heat", "Cool" or "Fan Only", manual switchover, Class I and II, Groups B, C, and D .....	1215.
/ EH(kw)	Auxiliary Electric Heat, (specify kw), for non-explosion proof models only .....	Contact Factory
/ SH(MBTUH)	Steam Heater, specify (MBTUH) and steam pressure, with control solenoid, less trap .....	Contact Factory
/ FDI	Disconnect Switch with Circuit Breaker Protection, installed .....	975.
/ DSI	Disconnect Switch, Explosion proof, non-fused, installed .....	825.
/ LAC	Low Ambient Control, for operating at ambient temperatures between 0 and 50 °F .....	285.
/ CC	<b>SaveCoil 101</b> oven baked coil coating on condenser and evaporator coils .....	1950.
/ EC	Full Corrosion Protection: All metal parts protected with epoxy; Coils protected w/ <b>SaveCoil 101</b> .....	3875.
/ EXP	Export Crate, heavy duty, for rough handling and marine shipment, approx. 400 lbs .....	640.
/ SRG	Supply Register and Return Air Filter Grille, extruded aluminum .....	150.

Your Representative is:



## How to Order

Model <sup>(1)</sup>	Cool	Heat <sup>(2)</sup>	Air Flow	Power	Fuse	Weight	Price
	BTUH	BTUH @ 47°F	CFM (E.S.P.)	Volts / Phase	Max. Amp	Ship Lbs.	US \$
VACX - 018 - B - ID2	18,300		650 (0.4)	208/230/1	20	350	
VACX - 024 - B - ID2	24,000		800 (0.2)	208/230/1	20	350	
VACX - 024 - C - ID2	24,000		800 (0.2)	208/230/3	15	350	
VACX - 036 - B - ID2	36,000		1100 (0.3)	208/230/1	35	400	
VACX - 036 - C - ID2	36,000		1100 (0.3)	208/230/3	25	400	
VACX - 036 - D - ID2	36,000		1100 (0.3)	460/3	15	400	
VACX - 048 - C - ID2	47,500		1550 (0.2)	208/230/3	35	550	
VACX - 048 - D - ID2	47,500		1550 (0.2)	460/3	15	550	
VACX - 060 - C - ID2	57,500		1700 (0.3)	208/230/3	45	550	
VACX - 060 - D - ID2	57,500		1700 (0.3)	460/3	20	550	
VACX - 018 - HP - 018 - B - ID2	19,000	18,800	650 (0.4)	208/230/1	20	350	
VACX - 024 - HP - 024 - B - ID2	23,600	23,200	800 (0.2)	208/230/1	20	350	
VACX - 024 - HP - 024 - C - ID2	23,600	23,200	800 (0.2)	208/230/3	15	350	
VACX - 036 - HP - 036 - B - ID2	35,600	34,400	1100 (0.3)	208/230/1	35	400	
VACX - 036 - HP - 036 - C - ID2	35,400	34,200	1100 (0.3)	208/230/3	25	400	
VACX - 036 - HP - 036 - D - ID2	35,400	34,200	1100 (0.3)	460/3	15	400	
VACX - 048 - HP - 048 - C - ID2	47,000	46,000	1550 (0.2)	208/230/3	35	550	
VACX - 048 - HP - 048 - D - ID2	47,000	46,000	1550 (0.2)	460/3	15	550	
VACX - 060 - HP - 060 - C - ID2	56,500	58,000	1700 (0.3)	208/230/3	45	550	
VACX - 060 - HP - 060 - D - ID2	56,500	58,000	1700 (0.3)	460/3	20	550	

(1) = Explosion Proof NEC Class I, Group D, Division 2. If specified otherwise, change "ID2" to new specification, e.g., "IC2".

(2) = Explosion proof heat pumps do not have supplemental electric heat. They are not recommended for use at outside ambients below 45°F.

## Dimensions

VACX	Width	Depth	Height	Supply Air Opening	Return Air Opening
	inches	inches	inches	inches	inches
-018, -024	30	18-1/4	66-1/2	8 H x 20 W	12 H x 20 W
-036,	38	18-1/4	66	8 H x 28 W	14 H x 28 W
-048, 060	43	22	81-5/8	10 H x 30 W	16 H x 30 W

## Accessories and Options

TCXP-C-1101	Thermostat, "Cool" or "Fan Only", Class I and II, Groups B, C and D .....	
TCXP-HC-1101	Thermostat, "Heat", "Cool" or "Fan Only", manual switchover, Class I and II, Groups B, C, and D .....	
/ EH(kw)	Auxiliary Electric Heat, (specify kw), for non-explosion proof models only .....	Contact Factory
/ SH(MBTUH)	Steam Heater, specify (MBTUH) and steam pressure, with control solenoid, less trap .....	Contact Factory
/ FDI	Disconnect Switch with Circuit Breaker Protection, installed .....	
/ DSI	Disconnect Switch, Explosion proof, non-fused, installed .....	
/ LAC	Low Ambient Control, for operating at ambient temperatures between 0 and 50 °F .....	
/ CC	<b>SaveCoil 101</b> oven baked coil coating on condenser and evaporator coils .....	
/ EC	Full Corrosion Protection: All metal parts protected with epoxy; Coils protected w/ <b>SaveCoil 101</b> .....	
/ EXP	Export Crate, heavy duty, for rough handling and marine shipment, approx. 400 lbs .....	
/ SRG	Supply Register and Return Air Filter Grille, extruded aluminum .....	

Your Representative is: